



Date of issue : 05/01/2005
Last. mod. date : 05/08/2010

Product code

**02338 RI-1110/145 EMBOSSED BLACK VINYL AP906
WKPE150 RIT/GRY**

Description

Embossed vinyl film with excellent outdoor and abrasion resistance.

As a rule it is not printed.

Permanent adhesive with high adhesion and shear at high temperature too. Suitable for outdoor applications. Not suitable for apolar substrates (PE,PP).

For decoration and lining in the automotive industry.

FACE MATERIAL

Type	Plasticised polymeric PVC
Colour and Finish	Black embossed matt
Weight	185 g/m ²
Thickness	145 μ

ADHESIVE

Reference	AP 906
Type	Acrylic permanent
Min. Appl. Temp.	+10°C
Service Temp.	-40°C/+140°C
Shear	Very high
Tack FTM9	15 N/inch ²
FinAdh FTM2	7 N/inch

RELEASE BACKING

Type	1 side silicone coated 2 side PE coated kraft
Colour and Finish	White
Weight	144 g/m ²
Thickness	170 μ

CHEMICAL RESISTANCE

Detergent	No effect (24 Hrs)
Gasoline	No effect (1 Hrs)
SAE20 Motoroil	No effect (24 Hrs)
10% HCl	No effect (10 min)
10% NH4OH	No effect (10 min)

Storage

The material must be stored at a temperature of 22°C +/- 2°C and 50% +/- 5% of Relative Humidity. Do not expose to direct sun light.
The area must be dry and clean. Please keep the material in the original packaging when not used in order to protect it from dust and contaminations.

All values presented in this data sheet are typical. Ritrama's data sheets provide only the general characteristics of the Product. It is the responsibility of the Customer and/or End User to determine that the Product is fit for the purpose for which the Customer and/or End User wish to use it. Ritrama can give no guarantee beyond the information given in the data sheet.