



Ritrama S.p.A.
produzione materiale autoadesivo

via della Guerrina, 108 20052 Monza (MI) ITALIA <http://www.ritrama.it>
Tel.(+39) 039.839.215 Fax (+39) 039.834.718 e-mail: info@ritrama.it

Certificato n. 099 – Norma UNI-EN 29001

Automotive series

Date of issue: 24/06/2003

TECHNICAL SHEET

100 μ SILVER GLOSS PET

Product code: RI- 6791/100

Description: Silver gloss PET (top coated)
Printing methods: screenprinting.

Permanent adhesive with high adhesion and shear at high temperature too. Suitable for outdoor applications. Not Suitable for apolar substrates.(PE,PP).
For decoration and lining in the automotive industry.

For special applications.

TECHNICAL DATA

FACE MATERIAL

Type	Metallized PET TC
Colour and finish	Silver, ultra gloss
Thickness (ASTM D374-88)	100 \pm 5 μ
Shrinkage (Rit. 042)	0 %

ADHESIVE

Reference	RI ASP8A
Type	Permanent acrylic (solvent based)
Weight (FTM-12)	40 \pm 3g/m ²
Min.appl.Temp.	+ 10 °C
Service temp.	From -30 °C to +140 °C
Peel 10' s.s. (FTM-1)	> 14 N/inch
Peel 24h s.s. (FTM-1)	>16 N/inch
Quick Stick (FTM-9)	>14 N/inch
Shear s.s. (FTM-8)	>200 h

RELEASE BACKING

Type	Pet 100 μ 1 side siliconised
Colour	Clear
Weight (ISO 536)	140 g/sqm \pm 2%

CHEMICAL RESISTANCE

Detergent	No effect	(24H)
Gasoline	No effect	(1 H)
SAE20 Motoroil	No effect	(24 H)
10% HCl	No effect	(10min)
10% NH4OH	No effect	(10min)

All values presented in this data sheet are typical. The information is given in good faith but without warranty.