



Date of issue : 05/01/2005

Last. mod. date : 05/01/2005

Product code**RI-6291/50 ASP8A****Description**

Bright chrome top coated polyester with a brushed finish. Excellent dimensional stability.

Printing methods: screenprinting.

Permanent adhesive with high adhesion and shear at high temperature too. Suitable for outdoor applications. Not suitable for apolar substrates (PE,PP).

Substitutes metal nameplates, decorative labels.

Technical data**FACE MATERIAL**

Type	Top coated polyester
Colour and Finish	Silver brushed
Weight	70 g/m ²
Thickness	50 μ

ADHESIVE

Reference	RI-ASP8A
Type	Permanent acrylic (solvent based)
Min. Appl. Temp.	+5 °C
Service Temp.	-30 °C+140 °C
Cohesion	Very high
Tack	Medium
Ultimate Adhesion	Very high

RELEASE BACKING

Type	1 side siliconised polyester
Colour and Finish	Clear
Weight	140 g/m ²
Thickness	100 μ

CHEMICAL RESISTANCE

Detergent	Slight effect (24 Hrs)
Gasoline	Slight effect (1 Hrs)
SAE20 Motoroil	No effect (24 Hrs)
10% HCl	No effect (10 min)
10% NH4OH	No effect (10 min)

Storage

The material must be stored at a temperature of 22°C +/- 2°C and 50% +/- 5% of Relative Humidity. Do not expose to direct sun light.

The area must be dry and clean. Please keep the material in the original packaging when not use in order to protect it from dust and contaminations.

All values presented in this data sheet are typical. The information is given in good faith but without warranty. Purchasers should carefully assess the suitability of the product for their own specific application. All specifications are subject to change without prior notice.