



**Product Code**

**RI - 670/23 AP**

**Description**

Bright chrome top coated polyester with excellent dimensional stability.

Printing methods: solvent based and UV screen printing.

Permanent adhesive with very good adhesion on glass and on a wide variety of substrates, except for apolar (PE, PP).  
BGVV compliance (indirect food contact)

For high quality labels, fun stickers, appliances, nameplates, bicycles decorations.

**Technical Data**

**FACE MATERIAL**

Type	Top coated polyester
Colour and Finish	Bright silver metallised
Weight	33g/m <sup>2</sup>
Thickness	23μ

**ADHESIVE**

Reference	RI - AP
Type	Permanent acrylic
Min. Appl. Temp.	+10°C
Service Temp.	-30°C / +120°C
Cohesion	Excellent
Tack	Medium
Ultimate Adhesion	High

**RELEASE BACKING**

Type	1 side silicone coated 2 side PE coated kraft
Colour and Finish	White
Weight	144g/m <sup>2</sup>
Thickness	166μ

**CHEMICAL RESISTANCE**

Detergent	Hazy (24 Hrs)
Gasoline	Slight effect (1 Hrs)
SAE20 Motoroil	No effect (24 Hrs)
10% HCl	No effect (10 min)
10% NH4OH	No effect (10 min)

**Storage**

The material must be stored at a temperature of 22°C +/- 2°C and 50% +/- 5% of Relative Humidity. Do not expose to direct sun light.  
The area must be dry and clean. Please keep the material in the original packaging when not use in order to protect it from dust and contaminations.

All values presented in this data sheet are typical. The information is given in good faith but without warranty. Purchasers should carefully assess the suitability of the product for their own specific application. All specifications are subject to change without prior notice.