



Product Code

RI - 650 / 36 AP

Description

Matt chrome top coated polyester.

Printing methods: solvent based and UV screen printing.

Permanent adhesive with very good adhesion on glass and on a wide variety of substrates, except for apolar (PE, PP).
BGVV compliance (indirect food contact).

Applications include nameplates and appliance labels.
In RI-650/36 AP 25 (backing HR) version is designed for "stereo labels" promotional grade, realized with DOMES technology.

Technical Data

FACE MATERIAL

Type	Top coated polyester
Colour and Finish	Matt silver metallised
Weight	50g/m ²
Thickness	36μ

ADHESIVE

Reference	RI - AP
Type	Permanent acrylic
Min. Appl. Temp.	+10°C
Service Temp.	-30°C / +120°C
Cohesion	Excellent
Tack	Medium
Ultimate Adhesion	High

RELEASE BACKING

Type	1 side silicone coated 2 side PE coated kraft
Colour and Finish	White
Weight	144g/m ²
Thickness	170μ

CHEMICAL RESISTANCE

Detergent	No effect (24 Hrs)
Gasoline	No effect (1 Hrs)
SAE20 Motoroil	No effect (24 Hrs)
10% HCl	No effect (10 min)
10% NH4OH	No effect (10 min)

Storage

The material must be stored at a temperature of 22°C +/- 2°C and 50% +/- 5% of Relative Humidity.
Do not expose to direct sun light.
The area must be dry and clean. Please keep the material in the original packaging when not use in order to protect it from dust and contaminations.

All values presented in this data sheet are typical. The information is given in good faith but without warranty. Purchasers should carefully assess the suitability of the product for their own specific application. All specifications are subject to change without prior notice.