



Date of issue: 05/01/2005
Last mod. date: 23/04/2007

Product Code

DECOBUS

Description

Plasticised white vinyl film, semi-gloss, flexible and with good conformability.

Printing methods: Large format solvent based inkjet

Semi-permanent acrylic adhesive with a good initial tack and with easy repositioning.

Specially designed for decorative advertising on busses. Its very good break resistance allows an easy removal even for big size signs.

Technical Data

FACE MATERIAL

Type	Plasticised vinyl film
Colour and Finish	White , semi-gloss,
Weight	115g/m ²
Thickness	85μ

ADHESIVE

Reference	RI - ASP30
Type	Semi-permanent acrylic
Min. Appl. Temp.	+ 10°C
Service Temp.	-30°C/ +100°C
Cohesion	Good
Tack	Medium
Ultimate Adhesion	Medium

RELEASE BACKING

Type	1 side silicone coated 2 side PE coated Kraft
Colour and Finish	White
Weight	135g/m ²
Thickness	135μ

CHEMICAL RESISTANCE

Detergent	No effect (24 Hrs)
Gasoline	No effect (1 Hrs)
SAE20 Motoroil	No effect (24 Hrs)
10% HCl	No effect (10 min)
10% NH4OH	No effect (10 min)

Storage

The material must be stored at a temperature of 22°C +/- 2°C and 50% +/- 5% of Relative Humidity. Do not expose to direct sun light.

The area must be dry and clean. Please keep the material in the original packaging when not use in order to protect it from dust and contaminations.

All values presented in this data sheet are typical. The information is given in good faith but without warranty. Purchasers should carefully assess the suitability of the product for their own specific application. All specifications are subject to change without prior notice.

