

Item	Value or Conclusions	
PVCfilm	Composition	One way vision
	Thickness	160micron (0.16mm)
	Weight	110g/m ²
	Hole Size	1.60(mm)
	Hole Space	2.40(mm)
	Wrinking rata	< 1%
	Gloss	50
	Transparency rate	52%
	Adhesive	Durability
Adhesive Type		Half-removable,clear acrylic adhesive
UV resistance		Good
Applicable Temperature Range		- 15°C~50°C
Initial viscosity		Test while adhering to stainless steel, 330N/m.
Release Paper	Final viscosity	Test while adhering to stainless steel, 490N/m.
	Type	paper with one-side silicone backing
	Color	White
Storage Period	Weight	175g/ m ²
	Durability	year (Storage temperature of 22°C, relative humidity of 50~55%)
Applications	year (vertically hung)	
Attentions	by screen-printing or wide-format digital printing, it is applied to vehicle graphics, building murals, shopping mall, window advertising,etc.	
	Data above are updated results or conclusions of test by the manufacturer, allowing ±5%error. Our company is responsible for nothing but that the product is in accordance with above technical data and capability. We may make amendment to the relative data or conclusions without any notice	
Quality Guarantee	All products are manufactured with high-quality raw materials and advanced technology & equipment, guaranteed by serious & scientific quality control system. Should our products sold have any proved quality problem, we would accept unconditioned refund or change of goods. Compensation scope will be limited within certain products price. No salespeople or agents have the rights to provide guarantee or assurance beyond announcements above or any similar contracts	

Update : 2007-8-16

